















ردیف	مدل	تصویر	مشخصات	قیمت (تومان)
1	DH-HAC-HFW1400DP		<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V</p>	628,000
				
2	DH-HAC-HFW1400R-VF-IRE6		<p>1/3" CMOS, 4MP HDCVI IR Bullet Camera 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P Max 30fps@4MP HD and SD output switchable 2.7-13.5mm vari-focal lens Max. IR length 60m, Smart IR IP67, DC12V</p>	865,000
				
3	DH-HAC-HFW1400TP		<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V</p>	473,000
				
4	DH-HAC-HFW1400SP		<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>	490,000
				
5	DH-HAC-HFW2231DP		<p>1/2.8" CMOS , 2 MegaPixel 25/30fps@1080P, 25/30fps@720P Starlight, 120dB true WDR, 3DNR Max 30fps@1080P HD and SD output switchable 3.6mm fixed lens (6mm, 8mm, 12mm optional) Max. IR length 80m, Smart IR IP67, DC12V</p>	823,000
				
6	DH-HAC-HFW2231EP		<p>1/2.8" CMOS , 2 MegaPixel 25/30fps@1080P, 25/30fps@720P Starlight, 120dB true WDR, 3DNR Max 30fps@1080P HD and SD output switchable 3.6mm fixed lens (6mm optional) Max. IR length 40m, Smart IR IP67, DC12V</p>	770,000
				
7	DH-HAC-HFW1220RP-VF-IRE6		<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-13.5mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 60m, Smart IR IP67, DC12V</p>	723,000
				

8	HAC-HFW1220R-VF		<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-13.5mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>	700,000
				
9	DH-HAC-HFW1220DP		<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR IP67, DC12V</p>	468,000
				
10	DH-HAC-HFW1220BP-B		<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>	443,000
				
11	DH-HAC-HFW1220SP		<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>	351,000
				
12	DH-HAC-HDW1400R-VF		<p>1/3" CMOS, 4MegaPixel 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P Max 30fps@4MP HD and SD output switchable 2.7-13.5mm vari-focal lens Max. IR length 30m, Smart IR IP67, DC12V</p>	886,000
				
13	DH-HAC-HDW1400EMP-A		<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens Built-in Mic DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V</p>	535,000
				
14	DH-HAC-HDW1400EMP		<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V</p>	500,000
				
15	DH-HAC-HDW1400MP		<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>	468,000
				

16 DH-HAC-HDW1220R-VF



1/2.9" CMOS, 2 MegaPixel
25/30fps@1080P, 25/30/50/60fps@720P
Max 30fps@1080P
HD and SD output switchable
2.7-13.5mm vari-focal lens
Max. IR length 30m, Smart IR
IP67, DC12V

703,000

17 DH-HAC-HDW1220EMP-A



1/2.9" 2Megapixel CMOS
25/30fps@1080P, 25/30/50/60fps@720P
3.6mm fixed lens
Built-in Mic
HD and SD output switchable
Support OSD Menu
DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR
Max. IR LEDs length 50m, Smart IR
IP67, DC12V

377,000

18 DH-HAC-HDW1220EMP



1/2.9" 2Megapixel CMOS
25/30fps@1080P, 25/30/50/60fps@720P
3.6mm fixed lens
HD and SD output switchable
Support OSD Menu
DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR
Max. IR LEDs length 50m, Smart IR
IP67, DC12V

351,000

19 DH-HAC-HDW1220MP



1/2.9" 2Megapixel CMOS
25/30fps@1080P, 25/30/50/60fps@720P
3.6mm fixed lens
HD and SD output switchable
Support OSD Menu
DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR
Max. IR LEDs length 30m, Smart IR
IP67, DC12V

314,000

20 DH-SD59230I-HC



2MP 30x Starlight IR PTZ HDCVI Camera
1/2.8" Starvis CMOS
Max. 25/30fps @1080P(1920x1080) & 20/30/50/60fps @720P Resolution
4.5mm~135mm 30x optical zoom
WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus
Max 400°/s pan speed, 360° endless pan rotation
HD and SD switchable
Up to 300 presets, 5 auto scan, 8 tour, 5 pattern
Audio(in/out) 1 / 1
Built-in 2/1 Alarm in/out
IR Distance up to 150m
IP66, OSD

7,275,000

21 DH-SD59225I-HC-S2



1/2.8" 2Megapixel Exmor R CMOS
Max 25/30fps @1080P & 20/30/50/60fps @720P Resolution
4.8mm ~ 120mm 25x optical zoom
WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus
Max 400°/s pan speed, 360° endless pan rotation
Control over coaxial cable
1-channel BNC HDCVI/CVBS output (switchable)
Up to 300 presets, 5 auto scan, 8 tour, 5 pattern
Built-in 2/1 Alarm in/out
1 Audio Input , RS485
IR Distance up to 150m
IP66, OSD

5,660,000

22 DH-SD49225I-HC



2MP 25x Starlight IR PTZ HDCVI Camera
 1/2.8" 2Megapixel Exmor R CMOS
 25/30fps@1080P, 25/30/50/60fps@720P
 Powerful 25x optical zoom,Digital Zoom 16x,Focal Length
 4.8mm~120mm
 Starlight technology
 120dB true WDR, 3D DNR
 Max. 25/30fps@1080P, 25/30/50/60fps@720P
 IR distance up to 100m
 PTZ Mode 5 Pattern, 8 Tour, Auto Pan ,Auto Scan
 Noise Reduction Ultra DNR (2D/3D),IP66

4,020,000

23 XVR5104HS-4M



4 Channel Penta-brid 4MP Compact 1U Digital Video Recorder
 H.264+/H.264 video compression
 Max 24Mbps Incoming Bandwidth
 1 SATA Port, up to 8TB capacity
 Analog: 4 Channel, BNC
 HDCVI: 4MP, 1080P@25/30fps, 720P@50/60fps,
 720P@25/30fps
 AHD: 5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps
 TVI: 5MP, 3MP, 1080P@25/30, 720P@25/30fps
 IP Camera: 4+2 Channel, each channel up to 5MP
 Smart Search and Intelligent Video System
 Audio In/Out:1/1, RCA
 USB: 2 USB Ports (2 USB 2.0)
 RS485:1 Port, for PTZ Control

1,120,000

24 DHI-XVR5104HS-S2



4CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-
 Time Recorder
 4M-N/1080P@15fps , 1080N/720P@25fps
 H.264+/H.264 dual-stream video compression
 4CH: 1/4 Playback
 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5
 Megapixel(24 Mbps)]
 Support Smart Search and Intelligent Video System
 1 Audio Input / 1 Audio Output
 1 SATA Port , Up to 8 TB
 HDMI , VGA ,simultanous video Output
 RS485 for PTZ support
 2*USB 2.0
 10/100 Mbps LAN Interface
 P2P Support

812,000

25 DHI-XVR5108H-4KL



8Channel Penta-brid 4K Mini 1U Digital Video Recorder
 H.265+/H.265 dual-stream video compression
 Supports HDCVI/AHD/TVI/CVBS/IP video inputs
 Max 12/24 channels IP camera inputs, each channel up to 8MP;
 Max 48/96Mbps Incoming Bandwidth
 Smart Search and Intelligent Video System
 1 SATA Port, up to 10TB capacity
 Analog: 8 Channel, BNC
 HDCVI: 4K, 6MP, 4MP, 1080P@25/30fps, 720P@50/60fps,
 720P@25/30fps
 AHD: 5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps
 TVI: 5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps
 IP Camera: 8+4 Channel, each channel up to 8MP
 Audio In/Out: 1/1, RCA
 Smart Search and Intelligent Video System
 USB: 2 USB Ports (2 USB 2.0)
 RS485:1 Port, for PTZ Control

1,672,000

26 DHI-XVR5108HS-S2



8CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder
 4M-N/1080P@15fps , 1080N/720P@25fps
 H.264+/H.264 dual-stream video compression
 8CH:1/4/9 Playback
 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 5 Megapixel(48 Mbps)]
 Support Smart Search and Intelligent Video System
 1 Audio Input / 1 Audio Output
 1 SATA Port , Up to 8 TB
 HDMI , VGA ,simultaneous video Output
 RS485 for PTZ support
 2*USB 2.0
 10/100 Mbps LAN Interface
 P2P Support

1,288,000

27 DH-XVR5216A-S2



16CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder
 4M-N/1080P@15fps , 1080N/720P@25fps
 H.264+/H.264 dual-stream video compression
 1/4/9/16CH Playback
 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96 Mbps)]
 Support Smart Search and Intelligent Video System
 4/1 Audio In/Out, Alarm In/Out 16/3
 2 SATA Port , Up to 16 TB(2*8TB)
 HDMI , VGA ,simultaneous video Output
 RS485 for PTZ support
 2 USB Ports (1 USB 2.0 , 1 USB 3.0)
 10/100/1000 Mbps LAN Interface
 P2P Support

2,560,000

28 DH-XVR5216AN-S2



16CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder
 4M-N/1080P@15fps , 1080N/720P@25fps
 H.264+/H.264 dual-stream video compression
 1/4/9/16CH Playback
 Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96 Mbps)]
 Support Smart Search and Intelligent Video System
 1/1 Audio In/Out
 2 SATA Port , Up to 16 TB(2*8TB)
 HDMI , VGA ,simultaneous video Output
 RS485 for PTZ support
 2 USB Ports (1 USB 2.0 , 1 USB 3.0)
 10/100/1000 Mbps LAN Interface
 P2P Support

2,477,000

29 DHI- XVR5216AN-4KL



16 Channel Penta-brid 4K 1U Digital Video Recorder
 H.264+/H.264 dual-stream video compression
 Supports HDCVI/AHD/TVI/CVBS/IP video inputs
 Max 12/24 channels IP camera inputs, each channel up to 8MP
 Max 48/96Mbps Incoming Bandwidth
 Smart Search and Intelligent Video System
 2 SATA Ports, up to 8TB capacity for each disk
 HDCVI Camera Input: 4K, 4MP, 1080P@25/30fps,
 720P@50/60fps, 720P@25/30fps
 AHD: 5MP, 4MP, 3MP, 1080P@25/30, 720P@25/30fps
 Analog: 16 Channel, BNC
 TVI: 5MP, 3MP, 1080P@25/30, 720P@25/30fps
 IP Camera: 16+8 Channel, each channel up to 5MP
 Audio In/Out: 1/1, RCA
 Smart Search and Intelligent Video System
 USB: 2 USB Ports (2 USB 2.0)
 RS485:1 Port, for PTZ Control

3,160,000

30 DHI- XVR5416L



16 Channel Penta-brid 1080P Lite 1.5U Digital Video Recorder
 Embedded processor
 H.264+/H.264 dual-stream video compression
 Support HDCVI/AHD/TVI/CVBS/IP video inputs
 Max 24 channels IP camera inputs, each channel up to 5MP
 Max 96Mbps Incoming Bandwidth
 Smart Search and Intelligent Video System
 HDCVI : 16 Channel
 IP Camera: 16+8 Channel, each channel up to 5MP
 Audio In/Out: 4/1
 Two-way Talk: 1 Mic In, 1 Mic Out, BNC
 4 SATA Ports, up to 8TB capacity for each disk, eSATA 1 Port
 RS485: 1 Port, for PTZ Control
 Alarm In/Out 16/6 , 2 HDMI 1VGA, 1Lan(1000)

4,770,000



31 DHI- XVR5432L



32 Channel Penta-brid 1080P Lite 1.5U Digital Video Recorder
 Embedded processor
 H.264+/H.264 dual-stream video compression
 Support HDCVI/AHD/TVI/CVBS/IP video inputs
 Max 16 channels IP camera inputs, each channel up to 5MP
 Max 64Mbps Incoming Bandwidth
 Smart Search and Intelligent Video System
 HDCVI : 32 Channel
 IP Camera: 32 Channel, each channel up to 5MP
 Audio In/Out: 4/1
 Two-way Talk: 1 Mic In, 1 Mic Out, BNC
 4 SATA Ports, up to 8TB capacity for each disk, eSATA 1 Port
 RS485: 1 Port, for PTZ Control
 Alarm In/Out 16/6, 2 HDMI 1 VGA, 1 Lan(1000)

7,800,000



32 DHI- XVR5832S



32 Channel Penta-brid 1080P Lite 2U Digital Video Recorder
 Embedded processor
 H.264+/H.264 dual-stream video compression
 Support HDCVI/AHD/TVI/CVBS/IP video inputs
 Max 32 channels IP camera inputs, each channel up to 5MP
 Max 128Mbps Incoming Bandwidth
 8 SATA Ports, up to 8TB capacity for each disk
 eSATA: 1 Port
 Smart Search and Intelligent Video System
 HDCVI: 32 Channel
 IP Camera: 32 Channel, each channel up to 5MP
 Audio In/Out: 16 Audio In, 1 Audio Out, BNC
 Two-way Talk: 1 Mic In, 1 Mic Out, BNC
 USB: 4 USB Ports (2 USB 2.0 , 2 USB 3.0)
 RS465,RS422,RS232: 1 Port, for PTZ Control
 Alarm In/Out 16/6 , 2 HDMI 1 VGA, 2 Lan (1000)

8,900,000








33 DH-PFM906



7" IPS HD retina capacitive touch screen(1920*1200);
 Support IP, HDCVI/AHD/TVI/CVBS, SDI;
 Support HDMI Input/Output;
 Support PoE, DC12V 2A and USB5V 2A power out;
 Build-in 37Wh big capacity polymer lithium ion battery , which
 can last 10 hours for normal use;
 Support TDR(network cable/coaxial cable), UTP cable tester and
 hunting, optical cable VFL;
 Support digital multi-meter function;
 Support optical power meter test function

10,000,000

ردیف	مدل	تصویر	مشخصات	قیمت (تومان)
34	DH-PFA103		<p>Aesthetic design Material: aluminum Hanging mount adapter Dimension $\Phi 133\text{mm} \times 37\text{mm}$ ($\Phi 5.23'' \times 1.46''$) Pipe Thread G1 1/2'' Load Bearing 3.0kg(6.61lb) Weight 0.13kg(0.29lb) Color White</p>	105,000
35	DH-PFA120		<p>Aesthetic design Material: aluminum Water-proof junction box Dimension 115.0mmx160.0mmx38.8mm (4.53"x6.30"x1.53") Inch Thread M20(G1/2'')</p> <p>Load Bearing 7.0kg(15.43lb) Weight 0.53kg(1.17lb) Color White</p>	105,000
36	DH-PFB300C		<p>Material: Aluminum & PC Ceiling Mount Bracket Neat & Integrated design Dimension (W x H x D) $\Phi 133.6\text{mm} \times 235.5\text{mm}$ Pipe Thread G1 1/2'' Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Humidity 0~90% RH Load Bearing 7.0Kg</p>	137,000
37	DH-PFB300S		<p>Material: Aluminum Wall Mount Bracket Neat & Integrated design Dimension (W x H x D) 228mm(W) x 150mm(H) x 160mm(D) Pipe Thread 1" PF Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Humidity 0~90% RH Load Bearing 3.0Kg</p>	144,000
38	DH-PFA110		<p>Material: Aluminum Mount Adapter Neat & Integrated design Dimension (W x H x D) $\Phi 59\text{mm} \times 53\text{mm}$ Pipe Thread G1 1/2'' Operating Temperature $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Humidity 0~90% RH</p>	54,000

کلیه محصولات با پرچسب گارانتی طلایی و کارت گارانتی رستر سرویس ارائه میشود

