




























1.3MP HD TVI SERIES			
1	DS-2CE56C2T-VFIR3	1.3 Megapixel high-performance CMOS/Analog HD output, up to 720P resolution 2.8 – 12mm vari-focal lens/Up to 40m IR distance/IP66 weatherproof	
	<b>4,250,000</b>		
2	DS-2CE16C2T-VFIR3	1.3 Megapixel high-performance CMOS/Analog HD output, up to 720P resolution/2.8 – 12mm vari-focal lens/Up to 40m IR distance/IP66 weatherproof	
	<b>4,250,000</b>		
3	DS-2CE16C5T-VFIR3	1.27 Megapixel high-performance CMOS/Analog HD output, up to 720P resolution/2.8 - 12mm vari-focal lens/Up to 40m IR distance/IP66 weatherproof	
	<b>4,750,000</b>		
2MP HD TVI ECONOMIC SERIES			
4	DS-2CE56D0T-IRMM	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/3.6 mm fixed lens/Up to 20m IR distance/IP66 weatherproof	
	<b>2,990,000</b>		
5	DS-2CE56D0T-IR	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/Up to 20m IR distance/IP66 weatherproof	
	<b>3,300,000</b>		
6	DS-2CE56D0T-IRM	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/Up to 20m IR distance/IP66 weatherproof	
	<b>3,460,000</b>		
7	DS-2CE56D0T-IT1	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/EXIR technology, Up to 20m IR distance/IP66 weatherproof	
	<b>3,860,000</b>		
8	DS-2CE56D0T-IT3	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/EXIR technology, Up to 40m IR distance/IP66 weatherproof	
	<b>4,430,000</b>		
9	DS-2CE16D0T-IR	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/Up to 20m IR distance/IP66 weatherproof	
	<b>3,460,000</b>		










10	DS-2CE16D0T-IT1	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/EXIR technology, Up to 20m IR distance/IP66 weatherproof	
	<b>4,240,000</b>		
11	DS-2CE16D0T-IT3	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/EXIR technology, Up to 40m IR distance/IP66 weatherproof	
	<b>4,650,000</b>		
12	DS-2CE16D0T-IT5	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/EXIR technology, Up to 80m IR distance/IP66 weatherproof	
	<b>5,180,000</b>		
13	DS-2CE56D1T-VFIR3	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 – 12mm vari-focal lens/Up to 40m IR distance/IP66 weatherproof , OSD menu , Up the Coax	
	<b>8,350,000</b>		
14	DS-2CE16D0T-WL5	2 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/White supplement light (up to 50 m distance)/ IP66/Up the Coax(HIKVISION-C)	
	<b>6,750,000</b>		
15	DS-2CE16D0T-VFIR3E	2 MP high performance CMOS/1920 × 1080 resolution/2.8 mm to 12 mm vari-focal lens/Ture Day/Night/Up to 40 m IR distance/PoC.at/IP66/Up the coax (HIKVISION-C)	
	<b>8,560,000</b>		
16	DS-2CE56D0T-VFIR3E	2 MP high performance CMOS/1920 × 1080 resolution/2.8 mm to 12 mm vari-focal lens/Ture Day/Night/Up to 40 m IR distance/PoC.at/IP66/Up the coax (HIKVISION-C)	
	<b>8,560,000</b>		
<b>2MP HD TVI HIGH END SERIES</b>			
17	DS-2CE56D7T-IT3	2.0 Megapixel high-performance CMOS/Analog HD output, up to 1080P resolution/2.8 mm fixed lens/EXIR technology, Up to 40m IR distance/IP66 weatherproof , WDR , OSD menu, DNR, Up the Coax	
	<b>4,350,000</b>		
18	DS-2CE56D8T-ITM	2 Megapixel high-performance CMOS/1920 × 1080 resolution/2.8 mm fixed focal lens EXIR 2.0, Smart IR, up to 20 m IR distance/IP67 , Up the Coax , WDR, 3D DNR , Ultra-Low Light	
	<b>4,200,000</b>		










19	DS-2CE56D8T-IT1E	2 Megapixel high-performance CMOS/Ultra-Low Light/1920 × 1080 resolution/2.8 mm, 3.6 mm, 6 mm fixed focal lens/120 dB true WDR, 3D DNR/EXIR 2.0, Smart IR, up to 20 m IR distance/IP67/Up the Coax(HIKVISION-C)/PoC.af	
	<b>7,190,000</b>		
20	DS-2CE16D8T-ITE	2 Megapixel high-performance CMOS/1920 × 1080 resolution/2.8 mm fixed focal lens/EXIR 2.0, Smart IR, up to 20 m IR distance/IP67 , Up the Coax , WDR, 3D DNR , Ultra-Low Light , PoC	
	<b>6,850,000</b>		
21	DS-2CE16D8T-IT3E	2 Megapixel high-performance CMOS/1920 × 1080 resolution/2.8 mm fixed focal lens/EXIR 2.0, Smart IR , up to 20 m IR distance/IP67 , Up the Coax , PoC , Ultra-Low Light , WDR, 3D DNR	
	<b>8,210,000</b>		
22	DS-2CE16D8T-IT3ZE	2 Megapixel high-performance CMOS/Ultra-Low Light/1920 × 1080 resolution/Auto focus, 2.8-12mm motorized vari-focal lens/120 dB true/WDR, 3D DNR/EXIR 2.0, Smart IR, up to 40 m IR distance/IP67/Up the Coax(HIKVISION-C)	
	<b>13,690,000</b>		
<b>3MP HD TVI ECONOMIC SERIES</b>			
23	DS-2CE56F1T-ITM	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/True Day/Night/OSD menu, DNR, Smart IR/EXIR technology, up to 20m IR distance /IP66 weatherproof/Up the Coax(HIKVISION-C)	
	<b>4,040,000</b>		
24	DS-2CE56F1T-IT1	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/True Day/Night/OSD menu, DNR, Smart IR/EXIR technology, up to 20m IR distance /IP66 weatherproof/Up the Coax(HIKVISION-C)	
	<b>4,430,000</b>		
25	DS-2CE56F1T-IT3	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/True Day/Night/OSD menu, DNR, Smart IR/EXIR technology, up to 40m IR distance /IP66 weatherproof/Up the Coax(HIKVISION-C)	
	<b>4,690,000</b>		
26	DS-2CE16F1T-IT	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/True Day/Night/OSD menu, DNR, Smart IR/EXIR technology, up to 20m IR distance /IP66 weatherproof/Up the Coax(HIKVISION-C)	
	<b>4,040,000</b>		
27	DS-2CE16F1T-IT1	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/True Day/Night/OSD menu, DNR, Smart IR/EXIR technology, up to 20/40/80m IR distance /IP66 weatherproof/Up the Coax(HIKVISION-C)	
	<b>4,560,000</b>		

28	DS-2CE16F1T-IT3	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/OSD menu, DNR, Smart IR/EXIR technology, up to 40m IR distance /IP66 weatherproof , Up the Coax	
	<b>4,950,000</b>		
29	DS-2CE16F1T-IT5	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/OSD menu, DNR, Smart IR/EXIR technology, up to 80m IR distance /IP66 weatherproof , Up the Coax	
	<b>5,480,000</b>		
30	DS-2CE56F7T-IT3Z	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/2.8-12 mm motorized vari-focal lens/EXIR technology, up to 40m IR distance /IP66 weatherproof , Up the Coax , WDR , OSD menu , DNR	
	<b>17,110,000</b>		
31	DS-2CE16F7T-IT3Z	3 Megapixel high-performance CMOS/Analog HD output, up to 3MP resolution/2.8-12mm motorized vari-focal lens/True Day/Night/OSD menu, DNR, Smart IR/True WDR, up to 120dB/EXIR technology, up to 40m IR distance /IP66 weatherproof/Up the Coax(HIKVISION-C)	
	<b>17,110,000</b>		
<b>5MP HD TVI ECONOMIC SERIES</b>			
32	DS-2CE56H0T-ITMF	5 Megapixel high-performance CMOS/Analog HD output, up to 5MP resolution/True Day/Night/OSD menu, 2D DNR, DWDR/EXIR technology, up to 20m IR distance/IP67 weatherproof/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/Up the Coax(HIKVISION-C)	
	<b>5,310,000</b>		
33	DS-2CE56H0T-IT1F	5 Megapixel high-performance CMOS/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/True Day/Night/OSD menu, 2D DNR, DWDR/EXIR technology, up to 20m IR distance/IP67 weatherproof/2560 × 1944 resolution/Up the Coax(HIKVISION-C)	
	<b>5,990,000</b>		
34	DS-2CE56H0T-IT3F	5 Megapixel high-performance CMOS/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/True Day/Night/OSD menu, 2D DNR, DWDR/EXIR technology, up to 40m IR distance/IP67 weatherproof/2560 × 1944 resolution/Up the Coax(HIKVISION-C)	
	<b>6,500,000</b>		
35	DS-2CE16H0T-ITF	5 Megapixel high-performance CMOS/Analog HD output, up to 5MP resolution/True Day/Night/OSD menu, 2D DNR, DWDR/EXIR technology, up to 20m IR distance/IP67/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/Up the Coax(HIKVISION-C)	
	<b>5,650,000</b>		
36	DS-2CE16H0T-IT1F	5 Megapixel high-performance CMOS/Analog HD output, up to 5MP resolution/True Day/Night/OSD menu, 2D DNR, DWDR/EXIR technology, up to 20/40/80m IR distance/IP67/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/Up the Coax(HIKVISION-C)	
	<b>6,160,000</b>		










37	DS-2CE16H0T-IT3F	5 Megapixel high-performance CMOS/Analog HD output, up to 5MP resolution/True Day/Night/OSD menu, 2D DNR, DWDR/EXIR technology, up to 20/40/80m IR distance/IP67/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/Up the Coax(HIKVISION-C)	
	<b>6,850,000</b>		
38	DS-2CE16H0T-IT5F	5 Megapixel high-performance CMOS/Analog HD output, up to 5MP resolution/True Day/Night/OSD menu, 2D DNR, DWDR/EXIR technology, up to 20/40/80m IR distance/IP67/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/Up the Coax(HIKVISION-C)	
	<b>7,360,000</b>		
39	DS-2CE56H0T-IT3ZF	5 Megapixel high-performance CMOS/2560 × 1944 resolution/2.7-13.5mm motorized vari-focal lens/EXIR 2.0, smart IR, up to 40 m IR distance/OSD menu, 2D DNR, DWDR/IP67/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/Up the Coax(HIKVISION-C)	
	<b>11,460,000</b>		
40	DS-2CE16H0T-IT3ZF	5 Megapixel high-performance CMOS/2560 × 1944 resolution/2.7-13.5mm motorized vari-focal lens/EXIR 2.0, smart IR, up to 40 m IR distance/OSD menu, 2D DNR, DWDR/IP67/4 in 1 video output (switchable TVI/AHD/CVI/CVBS)/Up the Coax(HIKVISION-C)	
	<b>11,810,000</b>		
41	DS-2CC52H1T-FITS	5 Megapixel high-performance CMOS/Analog HD output, up to 5MP resolution/0.01Lux @ (F1.2,AGC ON), 0 Lux with IR/Built-in microphone, 1-ch audio output/Up the Coax , OSD menu , up to 20m IR Distance	
	<b>24,630,000</b>		
<b>4K HD TVI ECONOMIC SERIES</b>			
42	DS-2CE78U8T-IT3	8.29 Megapixel high-performance CMOS/Ultra-low light , 3840 × 2160 resolution/2.8 mm, 3.6 mm, 6 mm fixed focal lens/EXIR 2.0, smart IR, up to 60m IR distance /IP67 , WDR , 3D DNR , Up the Coax	
	<b>19,500,000</b>		
43	DS-2CE18U8T-IT3	8.29 Megapixel high-performance CMOS/Ultra-low light , 3840 × 2160 resolution/2.8 mm, 3.6 mm, 6 mm fixed focal lens/EXIR 2.0, smart IR, up to 60m IR distance /IP67 , WDR , 3D DNR , Up the Coax	
	<b>20,530,000</b>		
<b>HD TVI DVR SERIES</b>			
44	DS-7208HGHI-E2	H.264 & Dual-stream video compression/Support HD-TVI/analog/IP camera triple hybrid Full channel@ 720P resolution non real-time recording/ IP Video Input: 2-ch Up to 2MP resolution/Interface Type: 2 SATA Interfaces up to 12 TB capacity	
	<b>5,000,000</b>		
45	DS-7208HGHI-F1	H.264 , H264+ & Dual-stream video compression/Support HD-TVI/analog/IP camera triple hybrid/Supports 1080p lite of all channels/ IP Video Input: 2-ch Up to 2MP resolution/Interface Type: 1 SATA Interfaces up to 6 TB capacity	
	<b>6,200,000</b>		










46	DS-7208HGHI-F2	H.264 , H264+ & Dual-stream video compression/Support HD-TVI/analog/IP camera triple hybrid/Supports 1080p lite of all channels/ IP Video Input: 2-ch Up to 2MP resolution/Interface Type: 2 SATA Interfaces up to 12 TB capacity	
	<b>6,800,000</b>		
47	DS-7204HQHI-K1	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/Up to 4MP lite resolution for recording/Long distance transmission over UTP and coaxial cable/ 4-ch synchronous playback/1 HDD Up to 6TB	
	<b>11,130,000</b>		
48	DS-7208HQHI-K1	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/Up to 4MP lite resolution for recording/Long distance transmission over UTP and coaxial cable/ 8-ch synchronous playback/1 HDD Up to 6TB	
	<b>15,760,000</b>		
49	DS-7216HQHI-K1	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/Up to 4MP lite resolution for recording/HDMI output at up to 4K (3840 × 2160) resolution for DS-7216HQHI-K1/Long distance transmission over UTP and coaxial cable/ 16-ch synchronous playback/1 HDD Up to 6TB	
	<b>28,790,000</b>		
50	DS-7224HQHI-K2	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/Up to 4MP lite resolution for recording/HDMI output at up to 4K (3840 × 2160) resolution for DS-7216HQHI-K1/Long distance transmission over UTP and coaxial cable/ 16-ch synchronous playback/2 HDD Up to 6TB	
	<b>52,100,000</b>		
51	DS-7232HQHI-K2	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/Up to 4MP lite resolution for recording/HDMI output at up to 4K (3840 × 2160) resolution for DS-7216HQHI-K1/Long distance transmission over UTP and coaxial cable/ 16-ch synchronous playback/2 HDD Up to 6TB	
	<b>55,450,000</b>		
52	DS-7204HUHI-K1	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/1-ch Connectable to H.265+/H.265 /H.264+/H.264 IP cameras/8 MP/5 MP/4 MP HDTV video input and live view for DS-7208HUHI-K1, and 5 MP/4 MP for DS-7204HUHI-K1/Long distance transmission over UTP and coaxial cable/4-ch synchronous playback/1 HDD Up to 6TB	
	<b>16,780,000</b>		
53	DS-7204HUHI-K1/P	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/1-ch Connectable to H.265+/H.265 /H.264+/H.264 IP cameras/8 MP/5 MP/4 MP HDTV video input and live view for DS-7208HUHI-K1, and 5 MP/4 MP for DS-7204HUHI-K1/Long distance transmission over UTP and coaxial cable/4-ch synchronous playback/1 HDD Up to 6TB	
	<b>20,490,000</b>		
54	DS-7208HUHI-K1	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/8 MP/5 MP/4 MP HDTV video input and live view/Long distance transmission over UTP and coaxial cable/8-ch synchronous playback/1 HDD Up to 6TB	
	<b>25,610,000</b>		










55	DS-7208HUHI-K2/P	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/8 MP/5 MP/4 MP HDTV video input and live view/HDMI output at up to 4K (3840 × 2160)/Long distance transmission over UTP and coaxial cable/8-ch synchronous playback/2 HDD Up to 6TB	
	<b>37,440,000</b>		
56	DS-7216HUHI-K2	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264 for the sub-stream of analog cameras/Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/2-ch Connectable to H.265+/H.265/H.264+/H.264 IP cameras/8 MP/5 MP/4 MP HDTV video input and live view/HDMI output at up to 4K (3840 × 2160)/Long distance transmission over UTP and coaxial cable/16-ch synchronous playback/2 HDD Up to 6TB	
	<b>51,040,000</b>		
57	DS-7204HTHI-K1	Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/Up to 2-ch 8 MP IP cameras input/8 MP HDTV video input and live view/Defogging function enabled for the supported analog cameras/Long distance transmission over UTP and coaxial cable/H.265+/H.265/H.264+/H.264 encoding/Simultaneous HDMI/VGA output/4K (3840 × 2160) resolution/1 SATA interface (up to 8 TB capacity per HDD)/4-ch synchronous playback	
	<b>25,430,000</b>		
58	DS-7208HTHI-K2	Self-adaptive HDTV/HDCVI/AHD/CVBS signal input/Up to 4-ch 8 MP IP cameras input/8 MP HDTV video input and live view/Defogging function enabled for the supported analog cameras/Long distance transmission over UTP and coaxial cable/H.265+/H.265/H.264+/H.264 encoding/Simultaneous HDMI/VGA output/4K (3840 × 2160) resolution/2 SATA interface (up to 8 TB capacity per HDD)/8-ch synchronous playback	
	<b>49,450,000</b>		
<b>2MP IP CAMERA SERIES</b>			
59	DS-2CD2120F-I	2MP high resolution (1920 x 1080)/Micro SD/SDHC/SDXC slot, up to 128G/Angle of view: 106°(2.8mm)/3D DNR & DWDR & BLC/up to 30m IR , Vandal-proof , IP67 , PoE , H.264	
	<b>12,660,000</b>		
60	DS-2CD2020F-I	2MP high resolution (1920 x 1080)/Micro SD/SDHC/SDXC slot, up to 128G/Angle of view: 85°(4mm)/3D DNR & DWDR & BLC/up to 30m IR , Vandal-proof , IP67 , PoE , H.264	
	<b>12,660,000</b>		
61	DS-2CD1123G0-I	Resolution: 2 MP (1920 x 1080)/2.8 mm / 114° lens/H.265+/H.265/H.264+/H.264/MJPEG video compression/3D-DNR, DWDR, BLC video processing functions/Access via Hik-Connect app/Region of interest (ROI)/Mechanically switching IR filter/IK10 rating (vandal-proof)/IP67 rating/Power: 12 VDC or PoE (802.3af)	
	<b>10,440,000</b>		
62	DS-2CD1023G0-I	Resolution: 2 MP (1920 x 1080)/2.8 mm / 103° lens/IR illuminator with range up to 30 m (EXIR 2.0)/H.265+/H.265/H.264+/H.264/MJPEG video compression/3D-DNR, DWDR, BLC video processing functions/Access via Hik-Connect app/ Region of interest / Mechanically switching IR filter/IP67 rating/Power: 12 VDC or PoE (802.3af)	
	<b>9,750,000</b>		
63	DS-2CD2720F-I	2MP high resolution/HD real-time video/IR LEDs: up to 30m/DWDR & 3D DNR & BLC/Onboard storage (up to 128GB)	
	<b>18,970,000</b>		










64	DS-2CD2420F-IW	HD1080P Video/Up to 10m / DWDR/3D DNR/BLC/ Support On-board Storage, up to 128GB/Built-in Wi-Fi optional	
	<b>12,630,000</b>		
<b>4MP IP CAMERA SERIES</b>			
65	DS-2CD2142FWD-IS	Up to 4MP (2688×1520) high resolution/Angle of view: 106° (2.8mm)/Micro SD/SDHC/SDXC slot, up to 128 GB/3D DNR , WDR , BLC , Up to 30m IR , Audio I/O/IP67 , Vandal-proof housing (IK10) , PoE	
	<b>17,620,000</b>		
66	DS-2CD2143G0-IS	Up to 4MP (2688×1520) high resolution/Angle of view: 106° (2.8mm)/Micro SD/SDHC/SDXC slot, up to 128 GB/3D DNR , WDR , BLC , Up to 30m IR , Audio I/O/IP67 , Vandal-proof housing (IK10) , PoE , H264+	
	<b>17,779,000</b>		
67	DS-2CD2342WD-I	Up to 4MP (2688×1520) high resolution/Angle of view: 106° (2.8mm)/Micro SD/SDHC/SDXC slot, up to 128 GB/3D DNR , WDR , BLC , Up to 30m IR , Audio I/O IP67 , PoE , H265+	
	<b>16,830,000</b>		
68	DS-2CD2542FWD-IS	Up to 4 megapixel high resolution/Full HD1080p video/Dual stream/2.8mm/4mm/6mm fixed lens/120dB Wide Dynamic Range/3D Digital Noise Reduction/3-axis adjustment/DC12V & PoE/Support H.264+/Up to 10m IR range/IP67 weather-proof protection/IK08 vandal-proof protection/ -S: Built-in microphone, Audio Output, Alarm IO	
	<b>23,690,000</b>		
69	DS-2CD1143G0-I	Up to 4MP (2688×1520) high resolution/Angle of view: 83° (4mm)/Micro SD/SDHC/SDXC slot, up to 128 GB/3D DNR , WDR , BLC , Up to 30m IR /IP67 , PoE , H265+	
	<b>14,030,000</b>		
70	DS-2CD2042WD-I	Up to 4MP (2688×1520) high resolution/Angle of view: 83° (4mm)/3D DNR , WDR , BLC , Up to 30m IR/IP67 , PoE , H264+	
	<b>16,000,000</b>		
71	DS-2CD2043G0-I	Up to 4MP (2688×1520) high resolution/Angle of view: 83° (4mm)/Micro SD/SDHC/SDXC slot, up to 128 GB/3D DNR , WDR , BLC , Up to 30m IR/IP67 , PoE , H265+	
	<b>16,250,000</b>		
72	DS-2CD2T42WD-I3	Up to 4MP (2688×1520) high resolution/Angle of view: 83° (4mm)/3D DNR , WDR , BLC /Up to 30m EXIR/IP67 , PoE , H264+	
	<b>16,500,000</b>		





















73	DS-2CD2T42WD-I8	1/3" Progressive Scan CMOS/Up to 4 megapixel resolution/120dB Wide Dynamic Range/3D DNR/EXIR high performance LEDs/Up to 80 meters IR range/12V DC±25% & PoE(802.3af Class3)/Support H.264+/IP67	
	<b>22,770,000</b>		
74	DS-2CD2T43G0-I5	Up to 4MP (2688×1520) high resolution/Angle of view: 83° (4mm)/Micro SD/SDHC/SDXC slot, up to 128 GB/3D DNR , WDR , BLC , Up to 50m IR ,/IP67 , PoE , H265+	
	<b>18,480,000</b>		
75	DS-2CD1043G0-I	Up to 4MP (2688×1520) high resolution/Angle of view: 83° (4mm)/Micro SD/SDHC/SDXC slot, up to 128 GB/3D DNR , DWDR , BLC , Up to 30m IR ,/IP67 , PoE , H265	
	<b>13,340,000</b>		
76	DS-2CD2742FWD-I	1/3" Progressive Scan CMOS/Up to 4 megapixel resolution/120dB WDR/3D DNR/Up to 30 meters IR range/Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB/Mobile Monitoring via Hik-Connect/12V DC±25% & PoE(802.3af Class3)/Support H.264+/IP67/IK10	
	<b>19,200,000</b>		
77	DS-2CD1743G0-I	1/3" progressive scan CMOS/3D DNR (Digital Noise Reduction)/2560 × 1440@20fps – 4mp/Up to 30 m IR range/2.8-12mm MotoZoom/PoE (Power over Ethernet)/H.265+, H.265, H.264+, H.264/IP67 – IK10/Dual stream/ Digital WDR (Wide Dynamic Range)/3-Axis adjustment	
	<b>21,550,000</b>		
78	DS-2CD2643G0-IZS	1/3" Progressive Scan CMOS/2688 ×1520@30fps/ 2.8 to 12 mm varifocal lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/Three streams/120dB WDR/2 Behavior analyses, and face detection/BLC/3D DNR/ROI/IP67, IK10/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/3-Axis adjustment	
	<b>35,920,000</b>		
79	DS-2CD2042WD-I	Up to 4.0 megapixel high resolution/Two video streams/2.8mm/2mm/4mm fixed lens/120 dB WDR/3D DNR/Support On-board Storage, up to 128GB/• 12VDC & POE(802.3af)/Up to 10m IR range/Alarm I/O/Support / Built-in Wi-Fi/Mobile Monitoring via Hik-Connect	
	<b>16,000,000</b>		
<b>5MP IP CAMERA SERIES</b>			
80	DS-2CD2152F-IS	0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/Up to 5 MP Resolution(2560×1920)/4mm, 6mm @ F2.0/H.264+, H.264, MJPEG/20 fps (2560 ×1920), 30fps (2048x1536,1920x1080,1280x720)/100 ft (30 m) 2 VDC ± 25%, PoE (802.3af)	
	<b>19,310,000</b>		
81	DS-2CD2052-I	Up to 5 megapixel high resolution/Electronic shutter/Dual video streams/Digital Wide Dynamic Range/3D Digital Noise Reduction/3-axis adjustment/DC12V & PoE/IR cut filter with auto switch/Up to 30m IR range/IP66 weather-proof protection/Mobile Monitoring via EZVIZ P2P or iVMS-4500	
	<b>18,350,000</b>		





82	DS-2CD2T52-I5	0.07Lux @ (F1.2, AGC ON) ,0 Lux with IR 0.1Lux @ (F1.4, AGC ON) ,0 Lux with IR/2560x1920/4mm@ F1.4 (6mm,optional)/H.264/MJPEG/H.264+ /50 meters IR/12 VDC ± 10%, PoE (802.3af)	
	<b>24,970,000</b>		
<b>6MP IP CAMERA SERIES</b>			
83	DS-2CD2163G0-I5	1/2.9" Progressive Scan CMOS/3072 x2048@20fps/2.8/4/6/8mm fixed len/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/2 Behavior analyse/120dB WDR/BLC/3D DNR/ROI/IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/30m IR	
	<b>26,680,000</b>		
84	DS-2CD2063G0-I	1/2.9" Progressive Scan CMOS/3072 x2048@20fps/2.8/4/6/8mm fixed lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/2 Behavior analyses/120dB WDR/BLC/3D DNR/ROI/ IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/30m IR	
	<b>19,500,000</b>		
85	DS-2CD2T63G0-I5	1/2.9" Progressive Scan CMOS/3072 x 2048@20fps/2.8/4/6/8mm fixed lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/120dB WDR/2 Behavior analyses/BLC/3D DNR/ROI/IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/50m IR	
	<b>22,240,000</b>		
86	DS-2CD2T63G0-I8	1/2.9" Progressive Scan CMOS/3072 x 2048@20fps/2.8/4/6/8mm fixed lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/120dB WDR/2 Behavior analyses/BLC/3D DNR/ROI/IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/80m IR	
	<b>23,610,000</b>		
87	DS-2CD2663G0-IZS	1/2.9" Progressive Scan CMOS/3072 x2048@20fps/2.8 to 12 mm varifocal / Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/120dB WDR/2 Behavior analyses, and face detection/BLC/3D DNR/ROI/IP67, IK10/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	
	<b>41,390,000</b>		
<b>4K IP CAMERA SERIES</b>			
88	DS-2CD2183G0-I5	1/2.5" Progressive Scan CMOS/3840 x2160@15fps/2.8/4/6/8mm fixed lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/2 Behavior analyses/120dB WDR/BLC/3D DNR/ROI/IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/30m IR	
	<b>24,970,000</b>		
89	DS-2CD2083G0-I	1/2.5" Progressive Scan CMOS/3840 x2160@15fps/2.8/4/6/8mm fixed lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/2 Behavior analyses/120dB WDR/BLC/3D DNR/ROI/IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/30m IR	
	<b>22,920,000</b>		
90	DS-2CD2T83G0-I5	1/2.5" Progressive Scan CMOS/3840 x 2160@15fps/2.8/4/6/8mm fixed lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/120dB WDR/2 Behavior analyses/BLC/3D DNR/ROI/IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/50m IR	
	<b>26,680,000</b>		

91	DS-2CD2T83G0-I8	1/2.5" Progressive Scan CMOS/3840 × 2160@15fps/2.8/4/6/8mm fixed lens/Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR/H.265+, H.265, H.264+, H.264/120dB WDR/2 Behavior analyses/BLC/3D DNR/ROI/IP67/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB/80m IR	
	<b>28,050,000</b>		
92	DS-2CD2683G0-IZS	1/2.5" Progressive Scan CMOS/840 × 2160@15fps/2.8 to 12 mm varifocal / Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR/ H.265+, H.265, H.264+, H.264/120dB WDR/2 Behavior analyses, and face detection/BLC/3D DNR/ROI/IP67, IK10/Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	
	<b>47,890,000</b>		
<b>SPECIAL IP CAMERA SERIES</b>			
93	DS-2CD2F52F-IS	Up to 5 megapixel high resolution/2.8mm/4mm/6mm fixed lens/Digital Wide Dynamic Range/3D Digital Noise Reduction/Support on-board storage, up to 128GB/DC12V & PoE/Up to 10m IR range	
	<b>18,750,000</b>		
94	DS-2CD2955FWD-IS	Up to 5 megapixel high resolution/2560 × 1920 @30fps/H.265, H.265+, H.264+, H.264/Support 14 display mode/FOV: horizontal FOV 180°, vertical FOV 180°/Dual video streams/DC12V & PoE (802.3af)/Digital Noise Reduction/Support on-board storage, up to 128 GB/Up to 8m IR range/Audio/Alarm IO	
	<b>54,780,000</b>		
95	DS-2CD2D14WD	0.028 lux @ (f/2.0, A GC on), 0 lux with IR/1280 × 720/ 2.8 mm @ f/2.0, Angle of view: 67.3°/H.264/MJPEG/60 Hz: 30 fps (1280 × 720), 30 fps (704 × 576), 30 fps (640 × 480)/12 VDC ± 10%	
	<b>13,090,000</b>		
96	DS-2CD2Q10FD-IW	1.0 Megapixel resolution/HD 720P real-time video/PIR detection/Support Wi-Fi/IR LEDs: up to 10m/Motorized Pan/Tilt rotation/ DWDR & 3D DNR & BLC/Intrusion Detection, Line Crossing Detection/Built-in Microphone & Speaker/Onboard storage (up to 64GB)	
	<b>16,720,000</b>		
97	DS-2CV2Q21FD-IW	Up to 2.0 megapixel high resolution/Two video streams/2.8mm fixed lens/Digital Wide Dynamic Range/3D Digital Noise Reduction/Build-in microphone and speaker, support two-way audio/Support on-board storage, up to 128 GB/Up to 5 m IR range/Built-in Wi-Fi/DC 5V ± 10 %, micro USB interface	
	<b>14,510,000</b>		
98	DS-2CV2U21FD-IW	Up to 2.0 megapixel high / Two video streams/2.8mm fixed lens/Digital Wide Dynamic Range/3D Digital Noise Reduction/Build-in microphone and speaker, support two-way audio/Support on-board storage, up to 128GB/Up to 10 m IR range/Built-in Wi-/ DC 5V ± 15 %, micro USB interface	
	<b>11,610,000</b>		
99	DS-2CD2E20F(-W)	Up to 1920x 1080 resolution 25fps(50Hz)-30fps(60Hz)/Efficient encoding capability/SupportSD/SDHC/SDXC card, up to 128GB/Tool-free installation/Support DC12V and PoE power supply/3D Digital Noise Reduction/Digital WDR/Dual-streams/Backlight Compensation/Support EZVIZ Cloud service/Built-in Wi-Fi optional/H.264	
	<b>18,650,000</b>		

NVR SERIES			
100	DS-7604NI-E1	Third-party network cameras supported/Up to 2 Megapixels resolution recording/HDMI and VGA output at up to 1920×1080P resolution/4-ch network cameras can be connected with 40M incoming bandwidth/Up to 1 SATA interfaces/Support network detection, including network delay, packet loss, etc.	
	<b>11,130,000</b>		
101	DS-7604NI-E1/4P	Third-party network cameras supported/Up to 2 Megapixels resolution recording/HDMI and VGA output at up to 1920×1080P resolution/4-ch network cameras can be connected with 40M incoming bandwidth/Up to 1 SATA interfaces/Support network detection, including network delay, packet loss, etc./4ch PoE	
	<b>15,920,000</b>		
102	DS-7604NI-Q1	Third-party network cameras supported/Up to 6 Megapixels resolution recording/HDMI and VGA output at up to 1920×1080P resolution/4-ch network cameras can be connected with 40M incoming bandwidth/Plug & Play with up to 4 independent PoE network interfaces/Support network detection, including network delay, packet loss, etc.	
	<b>12,500,000</b>		
103	DS-7604NI-Q1/4P	Third-party network cameras supported/Up to 6 Megapixels resolution recording/HDMI and VGA output at up to 1920×1080P resolution/4-ch network cameras can be connected with 40M incoming bandwidth/Plug & Play with up to 4 independent PoE network interfaces/Support network detection, including network delay, packet loss, etc./4ch PoE	
	<b>17,450,000</b>		
104	DS-7604NI-K1	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160)/4-ch network cameras can be connected with 40M incoming bandwidth/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search	
	<b>12,500,000</b>		
105	DS-7604NI-K1/4P	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160)/4-ch network cameras can be connected with 40M incoming bandwidth/Support dual-os to ensure high reliability of system running/Plug & Play with up to 4 independent PoE network interfaces/Support various VCA detection alarm and VCA search	
	<b>17,450,000</b>		
106	DS-7608NI-E2	Third-party network cameras supported/Up to 4 Megapixels resolution recording/HDMI and VGA output at up to 1920×1080P resolution/8-ch network cameras can be connected with 80M incoming, 80 outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay, packet loss, etc.	
	<b>15,580,000</b>		
107	DS-7608NI-E2/8P	Third-party network cameras supported/Up to 4 Megapixels resolution recording/HDMI and VGA output at up to 1920×1080P resolution/8-ch network cameras can be connected with 80M incoming, 80 outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay, packet loss, etc./8-ch PoE	
	<b>25,100,000</b>		
108	DS-7608NI-Q1	Third-party network cameras supported/Up to 8 Megapixels resolution recording/HDMI and VGA output at up to 4K resolution/8-ch network cameras can be connected with 80M incoming, 80 outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay, packet loss, etc.	
	<b>17,310,000</b>		

109	DS-7608NI-Q1/8P	Third-party network cameras supported/Up to 8 Megapixels resolution recording/HDMI and VGA output at up to 4K resolution/8-ch network cameras can be connected with 80M incoming, 80 outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay,packet loss, etc./8-ch PoE	
	<b>28,080,000</b>		
110	DS-7608NI-K2	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution/8-ch network cameras can be connected with 80M incoming, 160 outgoing bandwidth/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats	
	<b>19,080,000</b>		
111	DS-7608NI-K2/8P	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution/8-ch network cameras can be connected with 80M incoming, 160 outgoing bandwidth/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats/ 8-ch PoE	
	<b>30,200,000</b>		
112	DS-7616NI-E2	Third-party network cameras supported/Up to 6 Megapixels resolution / HDMI and VGA output at up to 1920x1080P resolution/ 16-ch network cameras can be connected with 160M incoming, 80M outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay, packet loss, etc.	
	<b>17,170,000</b>		
113	DS-7616NI-E2/8P	Third-party network cameras supported/Up to 6 Megapixels resolution / HDMI and VGA output at up to 1920x1080P resolution/16-ch network cameras can be connected with 160M incoming, 80M outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay, packet loss, etc./ 8-ch PoE	
	<b>26,320,000</b>		
114	DS-7616NI-E2/16P	Third-party network cameras supported/Up to 6 Megapixels resolution / HDMI and VGA output at up to 1920x1080P resolution/16-ch network cameras can be connected with 160M incoming, 80M outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay, packet loss, etc./ 16-ch PoE	
	<b>35,220,000</b>		
115	DS-7716NI-E4	Third-party network cameras supported/Up to 6 Megapixels resolution recording/HDMI and VGA output at up to 1920x1080P resolution/16-ch network cameras can be connected with 160M incoming, 80 outgoing bandwidth/Up to 4 SATA interfaces/Plug & play with up to 16 independent PoE network interfaces/Support network detection, including network delay, packet loss, etc	
	<b>37,500,000</b>		
116	DS-7716NI-E4/16P	Third-party network cameras supported/Up to 6 Megapixels resolution recording/HDMI and VGA output at up to 1920x1080P resolution/16-ch network cameras can be connected with 160M incoming, 80 outgoing bandwidth/Up to 4 SATA interfaces/Plug & play with up to 16 independent PoE network interfaces/Support network detection, including network delay, packet loss, etc/ 16-ch PoE	
	<b>37,440,000</b>		
117	DS-7616NI-Q1	Third-party network cameras supported/Up to 8 Megapixels resolution recording/HDMI and VGA output at up to 4K resolution/16-ch network cameras can be connected with 160M incoming, 80 outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay,packet loss, etc.	
	<b>18,000,000</b>		

118	DS-7616NI-Q2/16P	Third-party network cameras supported/Up to 8 Megapixels resolution recording/HDMI and VGA output at up to 4K resolution/16-ch network cameras can be connected with 160M incoming, 80 outgoing bandwidth/Up to 2 SATA interfaces/Support network detection, including network delay,packet loss, etc./16-ch PoE	
	<b>40,000,000</b>		
119	DS-7616NI-K2	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution/16-ch network cameras can be connected with 160M incoming, 160 outgoing bandwidth/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats	
	<b>20,670,000</b>		
120	DS-7616NI-K2/16P	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution/16-ch network cameras can be connected with 160M incoming, 160 outgoing bandwidth/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats/16-ch PoE	
	<b>40,000,000</b>		
121	DS-7716NI-K4	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160)resolution/16-ch network cameras can be connected with 160M incoming, 160 outgoing bandwidth/ Up to 4 SATA interfaces/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats	
	<b>46,270,000</b>		
122	DS-7716NI-K4/16P	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160)resolution/16-ch network cameras can be connected with 160M incoming, 160 outgoing bandwidth/ Up to 4 SATA interfaces/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats/16-ch PoE	
	<b>63,250,000</b>		
123	DS-7732NI-E4	Third-party network cameras supported/Up to 6 Megapixels resolution recording/HDMI and VGA output at up to 1920x1080P resolution/32-ch network cameras can be connected with 160M incoming, 80 outgoing bandwidth/Up to 4 SATA interfaces/Plug & play with up to 16 independent PoE network interfaces/Support network detection, including network delay, packet loss, etc	
	<b>49,100,000</b>		
124	DS-7732NI-E4/16P	Third-party network cameras supported/Up to 6 Megapixels resolution recording/HDMI and VGA output at up to 1920x1080P resolution/32-ch network cameras can be connected with 160M incoming, 80 outgoing bandwidth/Up to 4 SATA interfaces/Plug & play with up to 16 independent PoE network interfaces/Support network detection, including network delay, packet loss, etc/ 16-ch PoE	
	<b>67,030,000</b>		
125	DS-7732NI-K4	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160)resolution/32-ch network cameras can be connected with 256M incoming, 160 outgoing bandwidth/ Up to 4 SATA interfaces/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats	
	<b>58,280,000</b>		
126	DS-7732NI-K4/16P	Third-party network cameras supported/Up to 8 Megapixels resolution recording/Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160)resolution/32-ch network cameras can be connected with 256M incoming, 160 outgoing bandwidth/ Up to 4 SATA interfaces/Support dual-os to ensure high reliability of system running/Support various VCA detection alarm and VCA search/Support H.265/H.264/MPEG4 video formats/16-ch PoE	
	<b>74,130,000</b>		

PTZ CAMERA SERIES			
127	DS-2AE5223TI-A	2MP CMOS Image Sensor/1920x1080 /4-92mm focal lens 23X optical zoom/16X digital zoom/ DWDR/ Up to 150m IR distance/ 3D intelligent positioning Turbo HD and CVBS dual output IP66 standard	
	<b>57,950,000</b>		
128	DS-2AE7230TI-A	1/2.8" HD progressive scan CMOS/1920 × 1080 resolution 32× optical zoom, 16× digital zoom 120 dB true WDR (Wide Dynamic Range) Up to 150 m IR distance /3D intelligent positioning Switchable TVI/AHD/CVI/CVBS video outputs	
	<b>74,170,000</b>		
129	DS-2DE4220IW-DE	1/2.8" Progressive Scan CMOS / 1920 x 1080 Focal Length 4.7-94.0mm 20X Optical Zoom DWDR / 3D intelligent positioning function / Support cloud P2P Up to 100m IR distance / 12VDC & POE(802.3at)	
	<b>58,840,000</b>		
130	DS-2DE5220IW-AE	1/2.8" Progressive Scan CMOS/ Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom Digital WDR / 3D intelligent positioning function Up to 150 m IR distance Hi-PoE/24 VAC power supply / Support H.265 video compression	
	<b>97,830,000</b>		
131	DS-2DE5230IW-AE	1/3" Progressive Scan CMOS/ 1920x1080@25fps 4.3-129mm, 30x Optical Zoom , 16x Digital Zoom Onboard storage, up to 128GB/ Up to 150m IR distance 3D DNR / DWDR / 3D intelligent positioning function Support EZVIZ cloud P2P / PoE+ / 24VAC power supply H.264/MJPEG video compression/ IP66 standard	
	<b>101,930,000</b>		
132	DS-2DE7220IW-AE	1/2.8" Progressive Scan CMOS, up to 1920x1080@25fps Onboard storage, up to 128GB/ Up to 150m IR distance 4.7-94mm Lens 20X Optical Zoom , 16x Digital Zoom 3D DNR, D WDR/ 3D intelligent positioning H.264 / MJPEG/ IP66 / 24 VAC & Hi-PoE	
	<b>102,620,000</b>		
133	DS-2DE7230IW-AE	1/2.8" Progressive Scan CMOS, up to 1920x1080 Onboard storage, up to 128GB/ Up to 150m IR distance 4.3-129mm, 30x Optical Zoom , 16x Digital Zoom 3D DNR, D WDR/ 3D intelligent positioning H.264 / MJPEG/ IP66 / 24 VAC & Hi-PoE	
	<b>118,700,000</b>		
134	DS-2DE7420IW-AE	1/1.9" progressive scan CMOS/2560 × 1440@30fps Onboard storage, up to 128GB/ Up to 150m IR distance 4.7-94mm Lens 20X Optical Zoom , 16x Digital Zoom Defog, EIS, 3D DNR, BLC, HLC, Digital WDR 24 VAC & Hi-PoE Support H.265+/H.265 video compression	
	<b>142,300,000</b>		
135	DS-2DE7430IW-AE	1/1.9" progressive scan CMOS/2560 × 1440@30fps Onboard storage, up to 128GB/ Up to 150m IR distance 5.9-177 mm, 30x Optical Zoom , 16x Digital Zoom Defog, EIS, 3D DNR, BLC, HLC, Digital WDR 24 VAC & Hi-PoE Support H.265+/H.265 video compression	
	<b>156,270,000</b>		

136	DS-2DE7530IW-AE	1/1.9" progressive scan CMOS/2592×1944@30fps Onboard storage, up to 128GB/ Up to 150m IR distance 5.9-177 mm, 30x Optical Zoom , 16x Digital Zoom Defog, EIS, 3D DNR, BLC, HLC, Digital WDR 24 VAC & Hi-PoE Support H.265+/H.265 video compression	
	<b>175,120,000</b>		
137	DS-2DE4A220IW-DE	1/2.8" Progressive Scan CMOS/ Up to 1920 × 1080 resolution 4.7-94mm , 20× Optical Zoom, 16× Digital Zoom Digital WDR / 3D intelligent positioning function Up to 50 m IR distance Hi-PoE/24 VAC power supply / Support H.265 video compression	
	<b>75,260,000</b>		
138	DS-2PT3326IZ-DE3	<b>Panoramic Camera</b> 1/2.8" progressive scan CMOS / 3-ch1920 × 1080@30fps Support H.265 video compression / Horizontal FOV: 128.5° × 3	
	<b>77,970,000</b>	<b>PTZ Camera</b> 1/2.8" progressive scan CMOS / 1920 × 1080@30fps 2.8 mm to 12 mm, 4× optical zoom, 8× digital zoom Horizontal FOV: 120° to 56.6° (wide - tele)	
139	DS-2DE2202I-DE3	<b>Panoramic Camera</b> 1/2.8" progressive scan CMOS / 3-ch1920 × 1080@30fps Support H.265 video compression / Horizontal FOV: 128.5° × 3	
	<b>20,000,000</b>	<b>PTZ Camera</b> 1/2.8" progressive scan CMOS / 1920 × 1080@30fps 2.8 mm to 12 mm, 4× optical zoom, 8× digital zoom	
<b>HIKVISION EQUIPMENTS</b>			
140	IPC-4300H		call
141	DS-TT-X41T-TESTER		call
142	POWER ADAPTOR 12V/1A		250,000
143	DS-1005KI		34,210,000
144	DS-1100KI		100,760,000
145	DS-1602ZJ		2,830,000
146	DS-1661ZJ		3,090,000
147	DS-1662ZJ		3,540,000
148	DS-1663ZJ		1,370,000
149	DS-1602ZJ-POLE		4,450,000
150	DS-1693ZJ		call
151	DS-1697ZJ		call
152	DS-1681ZJ		1,030,000



153	DS-1605ZJ		3,430,000
154	DS-1671ZJ-SD11		2,400,000
155	DS-1280ZJ-SD11		1,890,000
156	DS-2601ZJ		call
<b>EQUIPMENTS</b>			
157	12V/2A		280,000
158	12V/5A		call
159	12V/5A METAL		550,000
160	12V/10A		700,000
161	12V/15A		900,000
162	12V/20A		1,100,000
163	12V/30A		1,300,000
164	4UNIT/35		1,150,000
165	6UNIT/35+Fan+Power		1,850,000
166	7UNIT/45+Fan+Power		2,200,000
167	9UNIT/45+Fan+Power		2,400,000
168	9UNIT/60+Fan+Power		2,700,000
169	12UNIT/60		call
170	12UNIT/80		call
171	BNC ETTO		39,000
172	BNC		33,000
173	فیش برق نری/مادگی		15,000
174	تبدیل 1 به 4		120,000
175	سوکت شبکه بافو		80,000
176	سوکت شبکه AMP		20,000

177	سوکت شبکه KNET	30,000
178	سینی رک 45	350,000
179	سینی رک 60	450,000
180	فلکسی 13	call
181	فلکسی 16	call
182	فلکسی 21	call
183	کابل ترکیبی 0.5	19,000
184	کابل ترکیبی 0.5 درجه یک	23,000
185	کابل ترکیبی 0.75	call
186	کابل ترکیبی 0.75 درجه یک	27,000
187	کابل RG	17,000
188	کابل RG درجه یک	call
189	کابل شبکه لگراند	call
190	کابل شبکه نگزنس	call
191	کابل شبکه ورتینا	52,000
192	کابل شبکه هایک ویژن	55,000
193	DES-1005A	1,010,000
194	DES-1005D	call
195	DES-1008A	1,150,000
196	DES-1008D	call
197	DGS-1005A	1,800,000
198	DGS-1005D	call
199	DGS-1008A	2,900,000
200	DGS-1008D	call
201	TL-SF1005D	850,000

202	TL-SF-1008D		950,000
203	TL-SG-1008D		1,850,000
204	TL-SG-1008D		2,650,000
205	HDD SkyHawk 1TB		call
206	HDD SkyHawk 2TB		call
207	HDD SkyHawk 3TB		call
208	HDD SkyHawk 4TB		call
209	HDD SkyHawk 6TB		call
210	HDD SkyHawk 8TB		call
211	HDD Purple 1TB		call
212	HDD Purple 2TB		call
213	HDD Purple 3TB		call
214	HDD Purple 4TB		call
215	HDD Purple 6TB		call
216	HDD Purple 8TB		call